



POLAM-ELTA Sp. z o.o.

LED DIODES
LED CONTROL LAMPS
www.polamelta.com

Jerozolimskie Avenue 202
02-486 Warsaw, POLAND
phone: (+48) 22-837-22-07
fax (+48) 22-207-24-28
e-mail: polamelta@polamelta.com.pl

SQUARE DIODES IN THE CASING (CQL-5XX)

Nr	Type	Wave length	Lens colour	Luminosity [mcd] min - max	Angle of luminosity [degrees]	UF [V]	IF [mA] feed current
1.	CQL-531 (O)	610	Diffusive orange		120	1,9-2,00	20
2.	CQL-533 (R)	635	Diffusive red		120	1,8-1,9	20
3.	CQL-534 (B)	470	Diffusive blue		120	3,00-3,3	20
4.	CQL-535 (Y)	590	Diffusive yellow		120	2,00-2,1	20
5.	CQL-536 (G)	525/530	Diffusive green		120	3,00-3,3	20
6.	CQL-5100 (W)	X	Diffusive white		120	3,00-3,3	20
7.	CQL-517/WA (RG)	635	Diffusive white		120	2,00-2,1	20
		525/530				3,00-3,3	
8.	CQL-517/WK (RG)	635	Diffusive white		120	1,8-1,9	20
		525/530				3,00-3,3	
9.	CQL-518/WA (RY)	635	Diffusive white		120	2,00-2,1	20
		590				2,00-2,1	
10.	CQL-518/WK (RY)	635	Diffusive white		120	1,8-1,9	20
		590				2,00-2,1	
11.	CQL-519/WA (GY)	525/530	Diffusive white		120	3,00-3,3	20
		590				2,00-2,1	
12.	CQL-519/WK (GY)	525/530	Diffusive white		120	3,00-3,3	20
		590				2,00-2,1	
13.	CQL-510/WA (RGY)	635	Diffusive white		120	2,00-2,1	20
		525/530				3,00-3,3	
		590				2,00-2,1	
14.	CQL-510/WK (RGY)	635	Diffusive white		120	1,8-1,9	20
		525/530				3,00-3,3	
		590				2,00-2,1	
15.	CQL-510/WA (RGB)	635	Diffusive white		120	2,00-2,1	20
		525/530				3,00-3,3	
		470				3,00-3,3	
16.	CQL-510/WK (RGB)	635	Diffusive white		120	1,8-1,9	20
		525/530				3,00-3,3	
		470				3,00-3,3	

NB: There is a possibility to produce two- and three-colour diodes in all possible colour combinations of emitting light:

red λ = 630-635 nm

green λ = 525-530 nm

yellow λ = 590 nm

orange λ = 610 nm

blue λ = 470 nm

and **COMMON ANODE** or **COMMON CATHODE** versions

